

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20\text{ }^{\circ}\text{C}$ ,  $\geq +60\text{ }^{\circ}\text{C}$ .

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5\text{ dB}$ .

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275\text{ km/h}$ .

Operating temperature of the antenna should be  $\leq -20\text{ }^{\circ}\text{C}$ ,  $\geq +60\text{ }^{\circ}\text{C}$ .

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5\text{ dB}$ .

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275\text{ km/h}$ .

Operating temperature of the antenna should be  $\leq -20\text{ }^{\circ}\text{C}$ ,  $\geq +60\text{ }^{\circ}\text{C}$ .

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5\text{ dB}$ .

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275\text{ km/h}$ .

Operating temperature of the antenna should be  $\leq -20\text{ }^{\circ}\text{C}$ ,  $\geq +60\text{ }^{\circ}\text{C}$ .

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5\text{ dB}$ .

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275\text{ km/h}$ .

Operating temperature of the antenna should be  $\leq -20\text{ }^{\circ}\text{C}$ ,  $\geq +60\text{ }^{\circ}\text{C}$ .

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5\text{ dB}$ .

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275\text{ km/h}$ .

Operating temperature of the antenna should be  $\leq -20\text{ }^{\circ}\text{C}$ ,  $\geq +60\text{ }^{\circ}\text{C}$ .

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5\text{ dB}$ .

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275\text{ km/h}$ .

Operating temperature of the antenna should be  $\leq -20\text{ }^{\circ}\text{C}$ ,  $\geq +60\text{ }^{\circ}\text{C}$ .

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20\text{ }^{\circ}\text{C}$ ,  $\geq +60\text{ }^{\circ}\text{C}$ .

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5\text{ dB}$ .

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275\text{ km/h}$ .

Operating temperature of the antenna should be  $\leq -20\text{ }^{\circ}\text{C}$ ,  $\geq +60\text{ }^{\circ}\text{C}$ .

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5\text{ dB}$ .

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275\text{ km/h}$ .

Operating temperature of the antenna should be  $\leq -20\text{ }^{\circ}\text{C}$ ,  $\geq +60\text{ }^{\circ}\text{C}$ .

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5\text{ dB}$ .

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275\text{ km/h}$ .

Operating temperature of the antenna should be  $\leq -20\text{ }^{\circ}\text{C}$ ,  $\geq +60\text{ }^{\circ}\text{C}$ .

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.

frequency range of the antenna should be 50 MHz-6 GHz.

eccentricity of the antenna should be  $\leq \pm 5$  dB.

charakteristik of the antenna should be omnidirectional.

weight of the antenna should be Max 20 kg.

Diameter of the antenna should be Max 400 mm.

Wind resistance of the antenna should be  $\geq 275$  km/h.

Operating temperature of the antenna should be  $\leq -20$  °C,  $\geq +60$  °C.